

Size	90	125	160	200
<b>ARNOLD CLASSIC Hydraulic</b>	<b>010 010 090</b>	<b>010 010 125</b>	<b>010 010 160</b>	<b>010 010 200</b>
ARNOLD CLASSIC Hydraulic with power preset		010 110 125	010 110 160	010 110 200
ARNOLD CLASSIC Hydraulic with base	<b>010 011 090</b>	<b>010 011 125</b>	<b>010 011 160</b>	<b>010 011 200</b>
ARNOLD CLASSIC Hydraulic with base and power preset		010 111 125	010 111 160	010 012 200
<b>ARNOLD CLASSIC Hydraulic Straight</b>	<b>010 012 090</b>	<b>010 012 125</b>	<b>010 012 160</b>	<b>010 012 200</b>
ARNOLD CLASSIC Hydraulic Straight with power preset		010 112 125	010 112 160	010 112 200
<b>ARNOLD CLASSIC Hydraulic in 2 parts</b>			<b>010 013 160</b>	<b>010 013 200</b>
ARNOLD CLASSIC Hydraulic in 2 parts with power preset			010 113 160	010 113 200
Clamping force (kN)	25	40	50	80
A	355	425	570	680
B	417 - 574	477 - 687	570 - 872	716 - 1093
B (with power preset)		513 - 723	599 - 908	760 - 1137
B (in 2 parts)			564 - 1366	716 - 1568
B (in 2 parts with power preset)			599 - 1402	760 - 1612
C	52	65	80	97
C (Straight vice in 2 parts)	52	70	89	101
D	92,5	107,5	130,5	160,5
D (Straight vice in 2 parts)	92,5	112,5	139,5	164,5
E	90	125	160	200
J	25	45	85	105
J (in 2 parts)			25	27
K	95	125	175	225
K (in 2 parts)			115	147
M	20	20	20	20
N	40,5	42,5	50,5	63,5
S	162	197	252	302
U	126	155	200	250
V	14	18	18	22
Weight (kg)	13	26	51	94
<b>Base</b>	<b>800 450 090</b>	<b>800 450 125</b>	<b>800 450 160</b>	<b>800 450 200</b>
R	25	28	32	45
T	230	270	325	400
Weight (kg)	5	8	15	32
<b>Clampings</b>	<b>90</b>	<b>125</b>	<b>160</b>	<b>200</b>
Clamping field O1	0 - 80	0 - 105	0 - 155	0 - 205
Clamping field O2	75 - 154	100 - 205	150 - 305	165 - 370
Clamping field (in 2 parts) Omax			795	845
<b>Spare spindle</b>	<b>90</b>	<b>125</b>	<b>160</b>	<b>200</b>
ARNOLD CLASSIC Hydraulic	800 010 090	800 010 125	800 010 160	800 010 200
ARNOLD CLASSIC Hydraulic with power preset		800 110 125	800 110 160	800 110 200
ARNOLD CLASSIC Hydraulic with base	800 010 090	800 010 125	800 010 160	800 010 200
ARNOLD CLASSIC Hydraulic with base and power preset		800 110 125	800 110 160	800 110 200
ARNOLD CLASSIC Hidráulica recta	800 010 090	800 010 125	800 010 160	800 010 200
ARNOLD CLASSIC Hydraulic Straight with power preset		800 110 125	800 110 160	800 110 200
ARNOLD CLASSIC Hydraulic in 2 parts			800 010 160	800 010 160
ARNOLD CLASSIC Hydraulic in 2 parts with power preset			800 110 160	800 110 200


**Clamping possibilities**



Clamping field O1



Clamping field O2



Clamping field (in 2 parts) Omax